



Exceed™ Enable™ ExxonMobil™ LDPE

Differentiated, sustainable collation shrink films solutions

Differentiated, sustainable collation shrink films solutions can be created with Exceed™ and Enable™ performance polyethylene in combination with 50% of recycled PE as well as in formulations allowing 25% downgauging. These packaging solutions help brand owners protect their products and deliver them securely by providing an outstanding combination of stiffness and toughness, with excellent optics and shrink performance.

Converters can optimize their film formulations to meet the specific needs of different collation shrink packaging applications using:

- 50% recycled PE combined with virgin performance PE that maintain packaging quality and integrity.
- Virgin performance PE to deliver extreme performance and 25% downgauging, creating an opportunity to do more with less by reducing the thickness of films.

Applications

Products requiring tight, secure and sustainable collation shrink packaging such as:

- Bottled beverages
- Canned goods
- Health or beauty products
- Cleaning products

Key benefits

Manufacturing collation shrink films with ExxonMobil performance PE and ExxonMobil™ LDPE offers opportunities for converters and brand owners to achieve:



Extreme toughness, puncture and dart impact resistance for high package integrity



Downgauging opportunities of 25% for unit cost & weight reduction and lower logistics costs



Optimal clarity and gloss for shelf appeal and brand visibility, even with 50% recycled PE



Stiffness and holding force for product stability and protection




Comparable shrink performance with 50% recycled PE, including adjustable film shrink speed




Excellent reliability on high-speed packaging lines for increased output

Sustainable collation shrink films solutions with Exceed™ and Enable™ performance PE

Solutions with 50% recycled PE



Solutions allowing 25% downgauging



Fine-tuning the choice of virgin PE grades helps in obtaining the required properties:

- **Exceed 1327 vs Exceed 1018 skins:** Due to its higher density, Exceed 1327 delivers stiffness to the film, which is important to increase holding force and improve handling and cuttability of the film in its operations at the bottling plant.
- **Enable 4002** brings brings both a high density for holding force and a low melt index for shrink performance.

Enable & Exceed performance polymers based downgauging solution:

- Tailored high gloss collation shrink solutions with downgauging opportunities for higher holding force, better mechanical properties, controlled shrink and high stiffness.

Solutions with 50% recycled PE

	Market reference 50 µm BUR 3.2 3-layer film	50% PIR 50 µm BUR 3.2 3-layer film	50% PCR 50 µm BUR 3.2 3-layer film
Exceed 1018		●	
Exceed 1327			●
Enable 4002		●	●
ExxonMobil™ LDPE		●	
C4LL	●		
LDPE	●		
PIR*		●	
PCR**			●

(*) PIR : post-industrial recycle (also called pre-consumer recycle) and
(**) PCR : post-consumer recycle

Solutions allowing 25% downgauging

	Reference 40 µm 3-layer film	Solution 32 µm 3-layer film	Solution 30 µm 3-layer film
Exceed 1018		●	
Exceed 1327			●
Enable 2703		●	
Enable 4002			●
ExxonMobil™ HDPE		●	●
ExxonMobil LDPE		●	●
C4LL	●		
LDPE	●		

Optimum collation shrink films solutions - Driving the future. ExxonMobil performance polyethylene can help you differentiate your collation shrink films that are recyclable*, and play a leading role in promoting more circular economy.

(*) Packaging made from a single polymer structure is easier to recycle, in communities where programs and facilities to collect and recycle plastic films exist.

Contact us for more information: exxonmobilchemical.com/pe

ExxonMobil
Signature Polymers

Bring your impossible



E1220-502-E49

©2024 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

What's new: ExxonMobil Signature Polymers

All our polymers are now positioned under a single portfolio brand: Signature Polymers. The aim is to simplify our product architecture and naming to improve portfolio navigation for you. We would like to stress that our commitment to high quality products remains the same. The composition of the products are unchanged, it is only the names that updated. We will be making these modifications over the next few months, through mid 2025, so you will see both old and new grade names highlighted during that time.

Here's a quick overview of brands and grade names that will be changed in this document:

Legacy Commercial Name	New Commercial Name
Exceed™ 1018	Exceed m 1018
Exceed 1327	Exceed m 1327
Enable™ 2703	Exceed™ Flow m 0327
Enable 4002	Exceed™ Stiff+ m 0238

Want to see what's changed in our portfolio? Go to exxonmobilchemical.com/sptransform