

## The high purity and reliable solution for Oil Seed Extraction

Energy lives here™



### Exxsol™ Hexane is formulated to meet food contact standards.

For over 30 years, ExxonMobil Chemical has been providing solution-based expertise globally, helping processors effectively meet their most demanding extraction challenges.

ExxonMobil is committed to meeting your Exxsol Hexane needs through our global manufacturing and supply capabilities.

### We have you covered.



#### Effective Extraction

Our application and technology experience<sup>1</sup> points to total paraffin content as key to effective oil seed extraction performance.



#### High Purity

Exxsol Hexane meets stringent food contact and purity requirements.



#### Meets Industry Standards

Exxsol Hexane is manufactured in compliance with Good Manufacturing Practices (GMP), meeting regional-specific industry standards while also meeting the specifications of many equipment manufacturers.






Contact us today by scanning the QR Code or clicking at [exxonmobilchemical.com/oilseedextraction](https://www.exxonmobilchemical.com/oilseedextraction).



Technical question?

Connect directly with our technical experts at: [FluidsAnswerPerson@exxonmobil.com](mailto:FluidsAnswerPerson@exxonmobil.com)

## Engage our local contacts today with regard to regional-specific industry standards requirements.

		Typical Value	Method
 <p><b>Effective Extraction</b></p>	Distillation range	65 - 68 °C	ASTM D86
	Density	0.675 kg/L	ASTM D4052
	Total hexane	> 99%	ASTM D5134
 <p><b>High Purity</b></p>	Sulfur content	< 1 ppm	ASTM D5453
	Metals/Metalloids	< 100 ppm	ICPES
	Lead	< 1ppm	ICPES
 <p><b>Meets Industry Standards</b></p>	Benzene	< 1 ppm	UV
	Aromatics	< 0.001%	ASTM D5134
	Non volatile matter	0.25 mg/100mL	ASTM D1353

1 References available upon request.

©2021 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.