

A proven, safer and compliant alternative to Xylene

Upgrading your choice to Solvesso™ 100 for your Agrochemical formulations

The Agrochemical industry has a proven history of ingenuity and innovation in enabling yield improvements and farming efficiencies while simultaneously improving the safety, health and environmental impact of their solutions; all in response to the macro challenge of affordably and safely feeding the growing global population. ExxonMobil has been an integral part in helping the industry deliver these solutions through its Solvesso™ Fluids portfolio, a portfolio with a proven track record across a broad range of formulations. Conversion from Xylene to Solvesso 100 is one such example. Safe and proven, the choice of ExxonMobil Solvesso Fluids is obvious!

Safe		Solvesso 100	Xylene	Benefit
	Higher flash point	√	Ø	-Safer handling
Proven Performance	High solvency	\checkmark	\checkmark	-Optimal active ingredient loading
	High specific gravity	\checkmark	\checkmark	-High emulsion stability
	Lower evaporation rate	\checkmark	Ø	-Improved wetting and efficient active ingredient delivery
Compliant	No impact of restriction limits for AgChem (China) ¹	\checkmark	Ø	-No defined limit as to % content in emulsifiable concentrates ¹
	No limitations on tolerance exemptions ²	\checkmark	Ø	Freedom to formulate without regulatory constraintsSimplifies registration requirements

¹ China standard HG/T4576-2013 (Limit of Harmful Solvents of Emulsifiable Concentrate Pesticide). Proposed restriction limit "List of restricted/prohibited pesticide additives" (draft)

² 40 CFR 180.910



Contact us today on industry requirements in your region

Technical question? Connect directly with our technical experts at: FluidsAnswerPerson@exxonmobil.com For more information, please visit exxonmobilchemical.com/agriculture

2021 ExoomMobil: DecomMobil: DecomMobil Under Standball on the interlocking "X" device and other product or service names used herein are trademarks of ExoomMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExomMobil's prior written authorization. To the extent ExomMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and eaders, looters, disclaimers and other actual information. To the extent ExomMobil and the strateging and/or copying of this document, the user may do so only if the document is unaltered and and not the actual information. To the extent ExomMobil approximation in this document takes only to the named product or materials. When on in combination with any other product or materials. When our complexity is document relates only to the named product or materials when non in combination with any other product or materials. Whe actual complexity is document relates only to the named product or materials when non in combination with any other product or materials. When only complexity is document relates only to the named product or materials when non in combination with any other product or materials. When only complexity is the stand and any process in the stand the information or the arcound in the information in this document is on the and any process in the territise's of interest. We expressly disclaim or the arcdular product and any process in the territise or process, and we expressly disclaim any ortholid the end or product and any process in the territise's open ones expressly disclaim any contrary implication. The territise's "our" "Source Mobil Demices" our more of ExomMobil Territise. Source areas described. The stand and "sourcess in the information in this document is not an endorsement of any non-ExomMobil product or process, and we expressly disclaim any contrary implication. The territise's "our" "Sourcess' "sourcess' access and we corrary implicat