

tomorrow's
performance
today

High-performance shrink hood film solutions comprised of virgin resin or up to 70% recycled PE content



Excellent
stiffness and
toughness



Good transverse
direction
shrinkage



Outstanding
clarity



Downgauging
potential

ExxonMobil's polyethylene (PE) portfolio, including Exceed™ XP 6026, Enable™ 4002 and Enable 2703 performance polymers, delivers exceptional properties that can contribute to the high performance of shrink hood film solutions, whether comprised of virgin resin or with the incorporation of up to 70% recycled PE content. These high-performance shrink hood films are easy to process and provide downgauging opportunities for cost-effective solutions with sustainability benefits.

Beneficial attributes

- Excellent stiffness and toughness
- High holding force
- Excellent shrinkage in transverse direction (TD)
- Incorporation of up to 70% recycled PE content


Value

- Potential to reduce film usage (downgauge) without compromising performance
- Potential to improve pallet stability during transportation

ExxonMobil has collaborated with several value chain members during the development of the latest shrink hood films solution:



Virgin resin shrink hood solutions




70 µm solution with Enable™ 4002 and Enable 2703

A : Enable 2703, Enable 4002, LD 165, Antiblock

B : Enable 4002, LD 165

C : Enable 2703, Enable 4002, LD 165, Antiblock



80 µm solution with Exceed™ XP 6026, Enable 4002 and Enable 2703 (improved toughness)


A : Enable 2703, Enable 4002, LD 165, Antiblock

B : Exceed XP 6026, Enable 4002, LD 165

C : Enable 2703, Enable 4002, LD 165, Antiblock

Incorporating recycled PE content – shrink hood solutions

70% PCR* resin




90 µm solution with Exceed XP 6026 and Enable 4002

A : Exceed XP 6026, Enable 4002, PCR resin, Antiblock

B : Enable 4002, PCR resin

C : Exceed XP 6026, Enable 4002, PCR resin, Antiblock

50% PCR resin




90 µm solution with Enable 4002 and Enable 2703

A : Enable 2703, Enable 4002, LD 157, Antiblock

B : Enable 4002, PCR resin, LD 157

C : Enable 2703, Enable 4002, LD 157, Antiblock

30% PCR resin



70 µm solution with Enable 4002

A : Enable 4002, LD 165, Antiblock

B : Enable 4002, LD 165, PCR resin

C : Enable 4002, LD 165, Antiblock

*PCR: Post-consumer recycled content

Grade	Melt index (g/10 min)	Density g/cm ³	Slip / anti-block
Enable 2703MC	0.30	0.927	No
Enable 4002MC	0.25	0.940	No
Exceed XP 6026ML	0.20	0.916	No
LD 157 CW	0.60	0.931	No
LD 165 BW1	0.33	0.922	No



Why ExxonMobil PE? Why today?

tomorrow's
performance
today



What some might view as solutions that will only happen in the future, ExxonMobil PE is making possible today – through our innovative and reliable products, collaborative approach, technology leadership and support, and our unmatched global supply and resources. Learn more about how we're helping our customers create solutions with sustainability benefits. Why wait for tomorrow to advance your business today? Contact your ExxonMobil PE representative and begin experiencing tomorrow's performance today in your stretch hood films.

©2021 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

Contact us for more information:
exxonmobilchemical.com/pe

ExxonMobil