ExonMobil Synthetic base stocks

Empowering lower GHG emission solutions, together



INNOVATING

products with sustainability benefits

ADVANCING

climate solutions across the value chain

BUILDING

sustainability into major facilities

We provide solutions that support the lowering of GHG emissions* in the transportation and industrial sectors.

*Benefit compared to conventional petroleum-based VLSFO, calculated on an energy basis. Well-to-wake CO2 emissions reduction calculated using Directive 2009/30/EC of the European Parliament and of the Council Annex IV C. 1 and MEPC 66/21 Annex



Learn more! Visit our website by scanning the QR code >

Empowering the world's lower GHG emission ambitions through energy efficient, durable lubricant solutions

How can we help? By supplying base stocks and formulating finished lubricants that can improve fuel economy, offer the potential for enhanced energy efficiency and improved durability. Our products lubricate renewable energy assets, manufacturing facilities and support mobility electrification. This means potential enhanced efficiency, reduced power consumption and reduced GHG emission* benefits that can be incorporated into your product solutions, such as extending vehicle range, increasing energy efficiency, and improving oxidative stability for long

Synthetic base stocks can be leveraged in a wide range of applications from transportation to heavy industries, where their intrinsic performance attributes can deliver potential sustainability related benefits* along the value chain.













ICE and EV cars & trucks

Aviation

Mining

Lubricant features & benefits

Excellent low temperature performance

Superior oxidative stability

Very good corrosion control

Outstanding electrical properties and thermal transfer Enhanced frictional behavior

Low volatility

Extreme wear protection

Controlled molecular structure

*Potential sustainability benefit

Improving energy efficiency

Extended oil drain intervals for lower lubricant consumption and less waste

Enhanced equipment protection for reduced downtime and extended life

Better biodegradability for specific applications

Performance

We can collaborate with you to provide insights on how Synthetic base stocks performance characteristics enable the formulation of more efficient and more durable finished Lubricants in a wide range of applications.



gear oil





Engine oil





Grease

~13% coefficient of friction reduction comparing synthetic vs. mineral-based greases



Electric vehicle fluids



savings and lowers system temperature4



Wind turbine lubricants



energy efficiency, improved oil drain intervals



Readily or inherently biodegradable options



biodegradability in 28 days (OECD301B) for Esterex NP 343



Automotive gear oil

1%6 fuel efficiency

benefit

Single sample or two sample average determination

© 2023 Exxon Mobil Corporation has numerous affiliates, many with names that include ExxonMobil, Exxon, Mobil, Esso, and XTO. For convenience and simplicity, those terms and terms such as Corporation, company, our, we, and its are sometime used as abbreviated references to specific affiliates or affiliate groups. Abbreviated references describing global or regional operational organizations, and global or regional business lines are also sometimes used for convenience and simplicity. Nothing contained herein is intended to override the corporate separateness of affiliated companies. This presentation includes forward-looking statements. Actual future results, including project plans, schedules, capacities, production rates, scaling and expanding current research, the impacts of new technologies, and the creation of new sources of supply for industrial processes could differ materially due to: changes in market conditions; political or regulatory developments including obtaining necessary regulatory permits; restrictions in trade, travel or broader government responses to first or subsequent waves of CVIDI-19; further research and testing of performance measures; technical or operating factors; the outcome of commercial negotiations; unexpetending of the commercial negotiation of the commercial negotiations; unexpetending factors of the commercial negotiation of the commercial negotiation of the commercial negotiation of the commercial negotiation of the negot



 $^{^{1}}$ Efficiency determined using a proprietary worm gear rig, comparing this synthetic gear oil to a commercially available mineral oil of the same viscosity. Efficiency improvements will vary based on operating conditions and application. 20.5% fuel economy improvment reported comparing PV1811 results obtained on OW-20 candidates blended with Grp III+ base stock vs. a candidate containing 25% LVLV novel PAO and the balance being the same Grp III+ used in the comparative candidate

³CoF measurements based on ASTM D5707 method run on ISO VG 460 NLGI #1 grease candidates prepared with either mineral base stock or with PAO ⁴Based on WLTC efficiency gains vs. GR III reference fluid @ -7°C

Fuel efficiency of 75W-85 grade synthetic-based gear fluid measured in field test compared to 80W-90 grade commercially available reference fluid